Phoenix 200 MAX

High Capacity, Low Grain Refrigerant Dehumidifier

The Most Effective and Versatile Drying Device Made

The Phoenix 200 MAX is one of the most effective and versatile drying devices available on the market today. The 200 MAX removes more water and has more grain depression than other refrigerant dehumidifiers, even though it only requires 7.4 amps of electricity. When you combine this performance with the multiple ducting and air filtration options, it is easy to understand why the Phoenix 200 MAX is considered the ultimate in low grain refrigerant dehumidification.

PHOENIX RESTORATION EQUIPMENT

High-Efficiency Design



The term LGR (Low Grain Refrigerant) was created to describe the unique drying capabilities of the Phoenix 200 dehumidifier. Beginning with the original Phoenix 200, these units were known for delivering substantially drier air, as well as for drying areas to much lower specific humidity levels than conventional dehumidifiers. The Phoenix 200 MAX, an improved version of the original Phoenix 200, is the culmination of eight years of LGR manufacturing and design expertise.

As always, Phoenix dehumidifiers feature significant air filtration. This filtration dramatically improves the air quality in the areas being dried and assures the continued optimal performance of the refrigeration system.

The Phoenix 200 MAX offers multiple filter options. While MERV-6 and MERV-8 still can be used, Phoenix has raised the bar and now includes standard in all 200 MAX a 65% MERV-11. The optional 95% MERV-14 will remove particles as small as .3 microns.

Versatile and Durable

The multiple ducting options on the Phoenix 200 MAX allow for ducting both the intake air and the filtered and dehumidified supply air. This makes it possible to easily combine the Phoenix 200 MAX with a HEPA air scrubber, air conditioner or desiccant dehumidifier.

innovative



Features

- Improved water removal
 - 128 pints/day AHAM (80°F, 60%)
 - 30 gals/day maximum
- Improved grain depression The driest air from an LGR
- Multiple air filter options
 Standard 65% MERV-11, 57% MERV-8, or 95% MERV-14
- Multiple ducting options 12" intake, 10" layflat supply
- Less than 7.5 amps
 Removes the most pints of water per kilowatt
- Stainless steel cabinet

exceptional

- Internal pump with 30 feet of hose
- Five-year warranty on the sealed refrigeration system.

proven

PERFORMANCE





Phoenix 200 MAX

Specifications

Part No.	4029740		
Power	7.4 amps; 851 watts		
Water Removal	128 pints/day @ AHAM (80°F, 60%) 240 pints/day @ saturation 30 gallons/day maximum @ saturation		
Refrigerant Charge	1 lbs., 8 oz. R410a		
Blower	290 CFM Internal Condensate Pump with 20' lift, 30' vinyl hose		
Operating Range	33°F to 105°F		
Filters:	16" x 20" Standard 2" Pleated Media 65% MERV-11 Optional 4" Mini-Pleat Media 95% MERV-14 Optional 2" Pleated Media 30% MERV-8		
Duct Options	Intake – 12" Flex-Duct Supply – 10" Lay-Flat		
Warranty	Five years; First year 100% of Parts and Labor Second-fifth year 100% of Parts of sealed refrigeration system.		
Dimensions			
Width Height Depth Weight	Cabinet 20" 40" 18-1/4" 130 lb	w/Cart 24-1/4" 40" 21-3/8" 131 lb	Shipping 27-1/2" 45-1/2" 22" 160 lb
Popular Accessories And Replacement Filters			
4024969	16" x 20" x 2" Pleated Media 30% MERV-8 (Optional)		
4021475	16" x 20" x 2" 2" Pleated Media 65% MERV-11 (Standard)		
4022489	4" Mini-Pleat Media 95% MERV-14 (Optional)		
4024750	12" x 25' Intake Flex Duct		
4024935	10" x 250' Lay-flat Duct		
4030115	Reed LM-8000 Meter		
4026600	Phoenix Solution LGR Performance Amplifier		
4026734	Phoenix Shield Kit Phoenix Shield		



Driven by performance. Powered by design.™

4201 Lien Rd Madison, WI 53704

608-237-8400 1-800-533-7533



193/4" 211/4" 24"

Therma-Stor LLC 01/15 Specifications subject to change without notice.